

COMPACT COLOR PRINTER MODULE

FIELD OF THE INVENTION

The invention relates to a compact printer system able to print full-color, business card size documents from a device about the size of a pen. The system includes various hot-connectable modules that provide a range of functions. In particular the invention relates to a compact color printer that provides a print function for the compact printer system.

Reference may be had to co-pending applications claiming priority from Australian Provisional Patent Application number PQ0560 dated 25 May 1999. The co-pending applications describe related modules and methods for implementing the compact printer system. The co-pending applications are as follows:

002250 " 23757560 Sub A.1

USSN	Docket No.	Title
TBA	PP02	Modular Compact Printer System
TBA	PP03	Nozzle Capping Mechanism
TBA	PP04	Ink Cartridge for Compact Printer System
TBA	PP07	Controller for Printer Module
TBA	PP08	Camera Module for Compact Printer System
TBA	PP09	Image Processor for Camera Module
TBA	PP10	Memory Module for Compact Printer System
TBA	PP11	Effects Module for Compact Printer System
TBA	PP12	Effects Processor for Effects Module
TBA	PP13	Timer Module for Compact Printer System
TBA	PP15	Color Conversion Method for Compact Printer System
TBA	PP16	Method and Apparatus of Dithering
TBA	PP17	Method and Apparatus of Image Conversion

BACKGROUND OF THE INVENTION

Microelectronic manufacturing techniques have led to the miniaturization of numerous devices. Mobile phones, personal digital assistant devices, and digital cameras are very common examples of the miniaturization trend.

One device that has not seen the advantage of microelectronic manufacturing techniques is the printer. Commercially available printers are large compared to many of the devices they could support. For instance, it is impractical to carry a color printer for the purpose of instantly printing photographs taken with known compact digital cameras.

A compact printhead has been described in co-pending United States Patent Applications filed simultaneously to the present application and hereby incorporated

by cross reference:

Sub A2 >

USSN	Docket No.	Title
TBA	MJ62	Fluidic seal for an ink jet nozzle assembly
TBA	IJ52	Ink jet printhead having a moving nozzle with an externally arranged actuator
TBA	IJM52	Method of manufacture of an ink jet printhead having a moving nozzle with an externally arranged actuator
TBA	MJ63	Ink jet printhead nozzle array
TBA	MJ58	Nozzle guard for an ink jet printhead

SUMMARY OF THE INVENTION

In one form, the invention resides in a printer module for a compact printer system comprising:

an elongate body;

a stationary printhead housed within said body,

means for moving a printable media past said stationary printhead;

an ink reservoir within said body and communicating with said printhead;

means within said body for storing an image to be printed by said printhead; and

means for transferring said image to said printhead;

said printhead printing said image on substantially the full width of said printable media in a single pass.

Further features of the invention will be evident from the following description.

BRIEF DESCRIPTION OF THE DRAWINGS

In order to assist with describing preferred embodiments of the invention, reference will be made to the following figures in which:

FIG 1 is a printer module;

FIG 2 is a camera module;

FIG 3 is a memory module;

FIG 4 is a communication module;

FIG 5 is a flash module;

FIG 6 is a timer module;

FIG 7 is a laser module;

FIG 8 is an effects module;

FIG 9 is a characters module;

FIG 10 is an adaptor module;

FIG 11 is a pen module;

FIG 12 is a dispenser module;

FIG 13 is a first compact printer configuration;

5 FIG 14 is a second compact printer configuration;

FIG 15 is a third compact printer configuration;

FIG 16 is a fourth compact printer configuration;

FIG 17 is an exploded view of the Printer Module of FIG 1;

FIG 18 is a top view of the Printer Module with ink cartridge removed;

10 FIG 19 is a cross-sectional view through AA in FIG 18; and

FIG 20 is a block circuit diagram of a controller for the printer module.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to FIGs 1 to 12, there are shown various modules that together form
15 a compact printer system. Individual modules can be attached and detached from the
compact printer configuration to allow a user-definable solution to business-card sized
printing. Images can also be transferred from one compact printer to another without
the use of a secondary computer system. Modules have a minimal user-interface to
allow straightforward interaction.

20 A compact printer system configuration consists of a number of compact
printer modules connected together. Each compact printer module has a function that
contributes to the overall functionality of the particular compact printer configuration.
Each compact printer module is typically shaped like part of a pen, physically
connecting with other compact printer modules to form the complete pen-shaped
25 device. The length of the compact printer device depends on the number and type of
compact printer modules connected. The functionality of a compact printer
configuration depends on the compact printer modules in the given configuration.

The compact printer modules connect both physically and logically. The
physical connection allows modules to be connected in any order, and the logical
30 connection is taken care of by the compact printer Serial Bus - a bus that provides
power, allows the modules to self configure and provides for the transfer of data.

In terms of physical connection, most compact printer modules consist of a
central body, a male connector at one end, and a female connector at the other. Since
most modules have both a male and female connector, the modules can typically be

connected in any order. Certain modules only have a male or a female connector, but this is determined by the function of the module. Adaptor modules allow these single-connector modules to be connected at either end of a given compact printer configuration.

5 A four wire physical connection between all the compact printer modules provides the logical connection between them in the form of the compact printer Serial Bus. The compact printer Serial Bus provides power to each module, and provides the means by which data is transferred between modules. Importantly, the compact printer Serial Bus and accompanying protocol provides the means by which
10 the compact printer system auto-configures, reducing the user-interface burden on the end-user.

Compact printer modules can be grouped into three types:

- image processing modules including a Printer Module (FIG 1), a Camera Module (FIG 2), and a Memory Module (FIG 3). Image processing modules
15 are primarily what sets the compact printer system apart from other pen-like devices. Image processing modules capture, print, store or manipulate photographic images;
- housekeeping modules including an Adapter Module (FIG 10), an Effects Module (FIG 8), a Communications Module (FIG 4), and a Timer Module (FIG 6). Housekeeping modules provide services to other modules or extended
20 functionality to other modules; and
- isolated modules including a Pen Module (FIG 11) and a Laser Module (FIG 7). Isolated modules are those that attach to the compact printer system but are completely independent of any other module. They do not necessarily require power, and may even provide their own power. Isolated Modules are defined because
25 the functionality they provide is typically incorporated into other pen-like devices.

Although housekeeping modules and isolated modules are useful components in a compact printer system, they are extras in a system dedicated to image processing and photographic manipulation. Life size (1:1) illustrations of the compact printer modules are shown in FIGs 1 to 12, and example configurations produced by
30 connecting various modules together are shown in FIGs 13 to 16.

FIG 1 shows a printer module that incorporates a compact printhead described in co-pending United States Patent Applications listed in the Background section of this application, incorporated herewith by reference, and referred to herewith as a Memjet printhead. The Memjet printhead is a drop-on-demand 1600 dpi inkjet printer

that produces bi-level dots in up to 4 colors to produce a printed page of a particular width. Since the printhead prints dots at 1600 dpi, each dot is approximately 22.5µm in diameter, and spaced 15.875µm apart. Because the printing is bi-level, the input image should be dithered or error-diffused for best results. Typically a Memjet printhead for a particular application is page-width. This enables the printhead to be stationary and allows the paper to move past the printhead. A Memjet printhead is composed of a number of identical 1/2 inch Memjet segments.

The printer module 10 comprises a body 11 housing the Memjet printhead. Power is supplied by a three volt battery housed in battery compartment 12. The printhead is activated to commence printing when a business card (or similar sized printable media) is inserted into slot 13. Male connector 14 and female connector 15 facilitate connection of other modules to the printer module 10.

FIG 2 shows a camera module 20. The camera module provides a point-and-shoot camera component to the compact printer system as a means of capturing images. The camera module comprises a body 21 having a female connector 22. A lens 23 directs an image to an image sensor and specialized image processing chip within the camera 24. A conventional view finder 25 is provided as well as a lens cap 26. An image is captured when the Take button 27 is pushed. Captured images are transferred to the Printer Module 10 for subsequent printing, manipulation, or storage. The Camera Module also contains a self-timer mode similar to that found on regular cameras.

FIG 3 shows a Memory Module 30 comprising a body 31, LCD 32, IN button 33, OUT button 34 and SELECT button 35. The Memory Module 30 is a standard module used for storing photographic images captured by the Camera 20. The memory module stores 48 images, each of which can be accessed either at full resolution or at thumbnail resolution. Full resolution provides read and write access to individual images, and thumbnail resolution provides read access to 16 images at once in thumbnail form.

The Memory Module 30 attaches to other modules via a female connector 36 or male connector 37. The male and female connectors allow the module to be connected at either end of a configuration. Power is provided from the Printer Module 10 via the Serial Bus.

A Communications Module 40 is shown in FIG 4. The communications module 40 consists of a connector 41 and a cable 42 that terminates in an appropriate connector for a computer port, such as a USB port, RS232 serial port or parallel port. The Communications Module 40 allows the compact printer system to be connected to a computer. When so connected, images can be transferred between the computer and the various modules of the compact printer system. The communications module allows captured images to be downloaded to the computer, and new images for printing to be uploaded into the printer module 10.

A Flash Module 50 is shown in FIG 5. The Flash Module 50 is used to generate a flash with flash cell 51 when taking photographs with the Camera Module 20. The Flash Module attaches to other modules via female connector 52 and male connector 53. It contains its own power source. The Flash Module is automatically selected by the Camera Module when required. A simple switch allows the Flash Module to be explicitly turned off to maximize battery life.

FIG 6 shows a Timer Module 60 that is used to automate the taking of multiple photos with the Camera Module 20, each photo separated by a specific time interval. The captured photos are stored in Memory Module 30. Any flash requirements are handled by the Camera Module 20, and can therefore be ignored by the Timer Module. The Timer Module 60 consists of a body 61 housing a LCD 62, START/STOP button 63 and UNITS button 64. A SELECT button 65 allows the user to select time units and the number of units are set by UNITS button 64. The Timer Module 60 includes a male connector 66 and female connector 67. The Timer Module takes its power from the Printer Module 10 via the Serial Bus.

A Laser Module 70 is shown in FIG 7. The Laser Module 70 consists of a body 71 containing a conventional laser pointer operated by button 72. As the Laser Module is a terminal module it only has one connector, which in the example is a male connector 73. The Laser Module is an isolated module, in that it does not perform any image capture, storage, or processing. It exists as a functional addition to the compact printer system. It is provided because laser pointer services are typically incorporated into other pen-like devices. The Laser Module contains its own power supply and does not appear as a device on the Serial Bus.

The Effects Module shown in FIG 8 is an image processing module. It allows a user to select a number of effects and applies them to the current image stored in the Printer Module 10. The effects include borders, clip-art, captions, warps, color

changes, and painting styles. The Effects Module comprises a body 81 housing custom electronics and a LCD 82. A CHOOSE button 83 allows a user to choose between a number of different types of effects. A SELECT button 84 allows the user to select one effect from the number of effects of the chosen type. Pressing the APPLY button 85 applies the effect to image stored in the Printer Module 10. The Effects Module obtains power from the Serial Bus. Male connector 86 and female connector 87 allow the Effects Module to be connected to other compact printer system modules.

FIG 9 shows a Character Module 90 that is a special type of Effects Module (described above) that only contains character clip-art effects of a given topic or genre. Examples include The Simpsons®, Star Wars®, Batman®, and Dilbert® as well as company specific modules for McDonalds® etc. As such it is an image processing module. It consists of a body 91 housing custom electronics and a LCD 92. SELECT button 93 allows the user to choose the effect that is to be applied with APPLY button 94. The Character Module obtains power from the Serial Bus through male connector 95 and female connector 96.

The Adaptor Module 100, shown in FIG 10, is a female/female connector that allows connection between two modules that terminate in male connectors. A male/male connector (not shown) allows connection between two modules that terminate in female connectors. The Adaptor Module is a housekeeping module, in that it facilitates the use of other modules, and does not perform any specific processing of its own.

All "through" modules have a male connector at one end, and a female connector at the other end. The modules can therefore be chained together, with each module connected at either end of the chain. However some modules, such as the Laser Module 70, are terminating modules, and therefore have either a male or female connector only. Such single-connector modules can only be connected at one end of the chain. If two such modules are to be connected at the one time, an Adaptor Module 100 is required.

FIG 11 shows a Pen Module 110 which is a pen in a module form. It is an isolated module in that it attaches to the compact printer system but is completely independent of any other module. It does not consume or require any power. The Pen Module is defined because it is a convenient extension of a pen shaped, pen sized

device. It may also come with a cap 111. The cap may be used to keep terminating connectors clean in the case where the chain ends with a connector rather than a terminating module.

To assist with accurately feeding a business card sized print media into slot 13 of the printer module 10, a dispenser module 120 is provided as shown in FIG12. The dispenser module 120 comprises a body 121 that holds a store of business card sized print media. A Printer Module 10 locates into socket 122 on the dispenser module 120. When correctly aligned, a card dispensed from the dispenser module by slider 123 enters slot 13 and is printed.

In the sense that a minimum configuration compact printer system must be able to print out photos, a minimum compact printer configuration contains at least a Printer Module 10. The Printer Module holds a single photographic image that can be printed out via its Memjet printer. It also contains the 3V battery required to power the compact printer system.

In this minimum configuration, the user is only able to print out photos. Each time a user inserts a business card 130 into the slot in the Printer Module, the image in the Printer Module is printed onto the card. The same image is printed each time a business card is inserted into the printer. In this minimum configuration there is no way for a user to change the image that is printed. The dispenser module 120 can be used to feed cards 130 into the Printer Module with a minimum of fuss, as shown in FIG 13.

By connecting a Camera Module 20 to the minimum configuration compact printer system the user now has an instant printing digital camera in a pen, as shown in FIG 14. The Camera Module 20 provides the mechanism for capturing images and the Printer Module 10 provides the mechanism for printing them out. The battery in the Printer Module provides power for both the camera and the printer.

When the user presses the "Take" button 27 on the Camera Module 20, the image is captured by the camera 24 and transferred to the Printer Module 10. Each time a business card is inserted into the printer the captured image is printed out. If the user presses "Take" on the Camera Module again, the old image in the Printer Module is replaced by the new image.

If the Camera Module is subsequently detached from the compact printer system, the captured image remains in the Printer Module, and can be printed out as

many times as desired. The Camera Module is simply there to capture images to be placed in the Printer Module.

FIG 15 shows a further configuration in which a Memory Module 30 is connected to the configuration of FIG 14. In the embodiment of FIG 15, the user has the ability to transfer images between the Printer Module 10 and a storage area contained in the Memory Module 30. The user selects the image number on the Memory Module, and then either sends that image to the Printer Module (replacing whatever image was already stored there), or brings the current image from the Printer Module to the specified image number in the Memory Module. The Memory Module also provides a way of sending sets of thumbnail images to the Printer Module.

Multiple Memory Modules can be included in a given system, extending the number of images that can be stored. A given Memory Module can be disconnected from one compact printer system and connected to another for subsequent image printing.

With the Camera Module 20 attached to a Memory Module/Printer Module compact printer system, as shown in FIG 15, the user can "Take" an image with the Camera Module, then transfer it to the specified image number in the Memory Module. The captured images can then be printed out in any order.

By connecting a Communications Module 40 to the minimum configuration compact printer system, the user gains the ability to transfer images between a PC and the compact printer system. FIG 16 shows the configuration of FIG 15 with the addition of a Communications Module 40. The Communications Module makes the Printer Module 10 and any Memory Modules 30 visible to an external computer system. This allows the download or uploading of images. The communications module also allows computer control of any connected compact printer modules, such as the Camera Module 20.

In the general case, the Printer Module holds the "current" image, and the other modules function with respect to this central repository of the current image. The Printer Module is therefore the central location for image interchange in the compact printer system, and the Printer Module provides a service to other modules as specified by user interaction.

A given module may act as an image source. It therefore has the ability to transfer an image to the Printer Module. A different module may act as an image store. It therefore has the ability to read the image from the Printer Module. Some

modules act as both image store and image source. These modules can both read images from and write images to the Printer Module's current image.

The standard image type has a single conceptual definition. The image definition is derived from the physical attributes of the printhead used in the Printer Module. The printhead is 2 inches wide and prints at 1600dpi in cyan, magenta and yellow bi-level dots. Consequently a printed image from the compact printer system is 3200 bi-level dots wide.

The compact printer system prints on business card sized pages (85mm x 55mm). Since the printhead is 2 inches wide, the business cards are printed such that 1 line of dots is 2 inches. 2 inches is 50.8mm, leaving a 2mm edge on a standard business-card sized page. The length of the image is derived from the same card size with a 2mm edge. Consequently the printed image length is 81mm, which equals 5100 1600dpi dots. The printed area of a page is therefore 81mm x 51mm, or 5100 x 3200 dots.

To obtain an integral contone to bi-level ratio a contone resolution of 267 ppi (pixels per inch) is chosen. This yields a contone CMY page size of 850 x 534, and a contone to bi-level ratio of 1:6 in each dimension. This ratio of 1:6 provides no perceived loss of quality since the output image is bi-level.

The printhead prints dots in cyan, magenta, and yellow ink. The final output to the printed page must therefore be in the gamut of the printhead and take the attributes of the inks into account. It would at first seem reasonable to use the CMY color space to represent images. However, the printer's CMY color space does not have a linear response. This is definitely true of pigmented inks, and partially true for dye-based inks. The individual color profile of a particular device (input and output) can vary considerably. Image capture devices (such as digital cameras) typically work in RGB (red green blue) color space, and each sensor will have its own color response characteristics.

Consequently, to allow for accurate conversion, as well as to allow for future image sensors, inks, and printers, the CIE $L^*a^*b^*$ color model [CIE, 1986, CIE 15.2 Colorimetry: Technical Report (2nd Edition), Commission Internationale De l'Eclairage] is used for the compact printer system. $L^*a^*b^*$ is well defined, perceptually linear, and is a superset of other traditional color spaces (such as CMY, RGB, and HSV).

The Printer Module must therefore be capable of converting $L^*a^*b^*$ images to the particular peculiarities of its CMY color space. However, since the compact printer system allows for connectivity to PCs, it is quite reasonable to also allow highly accurate color matching between screen and printer to be performed on the PC.

5 However the printer driver or PC program must output $L^*a^*b^*$.

Each pixel of a compact printer image is therefore represented by 24 bits: 8 bits each of L^* , a^* , and b^* . The total image size is therefore 1,361,700 bytes (850 x 534 x 3).

10 Each image processing module is able to access the image stored in the Printer Module. The access is either to read the image from the Printer Module, or to write a new image to the Printer Module.

The communications protocol for image access to the Printer Module provides a choice of internal image organization. Images can be accessed either as 850 x 534 or as 534 x 850. They can also be accessed in interleaved or planar format. When
15 accessed as interleaved, each pixel in the image is read or written as 24 bits: 8 bits each of L^* , a^* , b^* . When accessed as planar, each of the color planes can be read or written independently. The entire image of L^* pixels, a^* pixels or b^* pixels can be read or written at a time.

Detailed views of the Printer Module 10 are shown in FIGs 17, 18 and 19. The
20 Printer Module 10 is the central module in the compact printer system. It contains a 2-inch Memjet printhead 16, a Cyan/Magenta/Yellow ink cartridge 17, the current image stored in flash memory on the printhead, and a power source in the form of a 3V battery 12a in the battery compartment 12. With regards to processing, the Printer Module 10 contains a controller chip (or chips) 101 that controls printing of the stored
25 image in high quality.

The Printer Module 10 can be used as a stand-alone printer of a single image (such as business cards), or can be used in conjunction with other modules to print a variety of images.

Looking in detail at FIG 17, the body 11 of the printer module is in three parts
30 being a lid 11a, base 11b and chassis 11c. Printhead 16 with filter 16a fits into the chassis 11c. Powered rollers 18a are driven by motor and gearbox 103. Neutral rollers 18b fit into ink cartridge 17 and guide a card past the printhead 16. Springs 18c (FIG 19) urge the neutral rollers 18b towards the powered rollers 18a. The ink cartridge 17 is located beyond the rollers 18 so that the card passes between the printhead 16 and

Serial bus 104 provides power and data between the printer module 10 and
5 other modules connected to male connector 14 and female connector 15. The serial
bus 104 picks up power from the battery 12a and signals from the controller 101.

10

15

20

25

- A QA chip in the ink cartridge keeps track of how much ink has been used.

30

PP01US

A schematic of a suitable controller 101 is shown in FIG 20. The controller may be embodied in a single application specific integrated circuit or in a number of discrete elements. The controller 101 includes a simple micro-controller CPU core 201 with associated program ROM 202 and program RAM 203. The CPU 201 communicates with the other units within the controller via memory-mapped I/O supported by a Memory Decoder 204. The Decoder 204 translates data addresses into internal controller register accesses over the internal low speed bus 205, and therefore allows for memory mapped I/O of controller registers. The bus 205 includes address lines 205a and data or control lines 205b.

An optional Serial Bus interface 206, is connected to the internal chip low-speed bus 205 and connects to the Serial Bus for communication with other modules. A parallel interface 207 provides communication to the motor and gearbox 103 in the printer module 10. It can also receive signals from buttons, such as a paper sensor 102.

There are two optional low-speed serial interfaces 208, 209 connected to the internal low-speed bus 205. A first interface 208 connects to the QA chip 220 in the ink cartridge of the printer module 10. The second interface connects to a QA chip 221 on the print module 10. The reason for having two interfaces is to connect to both the on-module QA Chip 221 and to the ink cartridge QA Chip 220 using separate lines to improve security. If only a single line is used, a clone ink cartridge manufacturer could usurp the authentication mechanism and provide a non-proprietary cartridge.

The total amount of memory required for the interleaved linear CMY/L*a*b* image is 1,361,700 bytes (approximately 1.3 MB). The image is written to Image Storage Memory 211 by the Image Access Unit 212, and read by both the Image Access Unit 212 and the Printhead Interface (PHI) 210. The CPU does not have direct random access to this image memory. It must access the image pixels via the Image Access Unit 212. The Printhead Interface 210 is the means by which the controller loads the printhead 16 with the dots to be printed, and controls the actual dot printing process.

The controller 101 may also include a clock phase-locked loop 213 that provides timing signals to the controller. The clock 213 draws a base signal from crystal oscillator 214. Some CPU include a clock so the clock and crystal would not be required.

A standard JTAG (Joint Test Action Group) Interface 215 is included in the controller for testing purposes. Due to the complexity of the controller, a variety of testing techniques are required, including BIST (Built In Self Test) and functional block isolation. An overhead of 10% in chip area is assumed for overall chip testing circuitry.

The battery used to power the compact printer system is a CR1/3N cell. The battery contains enough power to print 133 photos. The characteristics of the battery are listed in the following table.

Parameter	Value
Type Designation	CR1/3N
Voltage (V)	3
Electrochemical System	Lithium
Typical Capacity (mAh)	170
Height (mm)	10.80
Diameter (mm)	11.60
Weight (g)	3.00

Throughout the specification the aim has been to describe the preferred embodiments of the invention without limiting the invention to any one embodiment or specific collection of features. Persons skilled in the relevant art may realize variations from the specific embodiments that will nonetheless fall within the scope of the invention.